

Rotary Pump

Fluid Management Solution

RP90TEF

Plastic Teflon Rotary Pump



- Pump Type: Rotary VaneFlow: 300 ml / Rotation
- Maximum Fluid Temperature: 130°F / 54°C
- Mounting: 2" MNPT Bung AdapterSuction Tube Length: 40" Maximum
- Inlet: 1-1/4" O.D.
- Outlet: 1" O.D. Curved Spout
- · Wetted Parts: Pvdf
- •Maximum Viscosity: 2,000 SSU
- Standard Packing: 6pcs/ctn, NW: 16.5kgs, GW: 17.5kgs, Cuft: 2.2'
- Made from durable, light weight, rust resistance and high chemical resistance materials.
- Suitable for transferring most soluble, corrosive, volatile & edible liquids which are compatible with Teflon and Viton.
- Supply with 2" Bung adapter and 3-piece PVDF suction tube to fit most 15, 30 and 55 gallon drums.
- Self-priming unit, dispenses approximately 300 ml per stroke.
- · Liquids do not with dirt to ensure pump life.

Part No: RP90TEF

Wellington Head Office: 90 Sydney St, PO Box 38 720 Petone, Wellington, Tel: 64 4 568 4933, Fax: 64 4 568 4789 Email: sales@liquip.co.nz Website: www.liquip.co.nz

