



HP-100 Dual-Flo Petroleum Hand Pump

Information Sheet



The HP-100 Dual-Flo Hand Pump provides the ultimate economy in fuel transfer. This dependable, double-action piston pump provides a simple, reliable answer to on-site or field refuelling needs.

Specifications

The HP-100 Dual-Flo Petroleum Hand Pump is compatible with a wide variety of petroleum products and fits any container with a 2-inch NPT bung.

Construction Lightweight, die-cast aluminium housing. Stainless steel piston shaft and liner. Buna-N seals. Built-in anti-siphon valve to prevent leaks at the nozzle.

Pumping Capacity Up to 30 GPM (114 LPM)

Pumping Settings 2 litre setting for high volume, higher resistance.
1 litre setting for low volume, low resistance.

Inlet 1 inch FNPT
Outlet 3/4 inch FNPT
Dry Prime 5 ft. (1.5m) minimum.

Hose 3/4" x 8 ft. (2.4m) Buna-N
Nozzle Thermoplastic unleaded nozzle. Built-in nozzle holder.

Suction Pipe Plastic, adjustable 22 to 40 inches (56 to 102cm).

Security Handle can be padlocked.

Shipping Weight 18 lbs. (8.1kg)

PRICE: * \$



Wellington Head Office: 90 Sydney St, PO Box 38 720
Petone, Wellington, Tel: 64 4 568 4933, Fax: 64 4 568 4789
Email: sales@liquip.co.nz Website: www.liquip.co.nz