



M-150SA Series Electric Gear Pump

Information Sheet

12-volt Fuel Pump with Automatic Nozzle

Specifications

Applications

Fluids: Low viscosity petroleum fuels such as kerosene, and diesel fuel.

Operating Environment:

Outdoor, year-round with an operating temperature range of -20° to +125°F (-29° to +52°C). Designed for mounting on portable, vented fuel storage tanks.

Pump Housing:

Lightweight, corrosion-resistant, cast aluminium body. Convenient spin collar for easy installation

Performance

Pump Rate: Up to 8 GPM (30 LPM).
Duty Cycle: 30 minutes on, 30 minutes off.
Dry Prime: 4.8 ft. (1.5m) minimum.
Total Lift: 23 ft. (7m)
Current Draw: 18 amp

Electrical

Input: 12 volt DC
Cord: 15 ft. (4.6m) of 12 gauge
Fuse: 25 amps AGC
Motor: 1900 RPM. UL Listed. CSA Certified.

Mechanical Connections

Bung: 2 inch NPT
Inlet: 1 inch BSP
Outlet: 3/4 inch BSP

Accessories

Hose: 3/4 inch x 12 ft. (3.7m) Buna-N statically grounded.
Nozzle: 3/4 inch automatic shutoff, unleaded.

Security: Nozzle can be padlocked.

Ship Weight: 24 lbs. (10.8kg)

PRICE: * \$



Look at total value and you'll agree this is the best 12-volt portable fuel pump on the market. Hundreds of thousands of similar GPI light-duty gear pumps have given years of dependable service.

Model M-150SA is a 12-volt gear pump with an automatic shutoff unleaded nozzle.



Wellington Head Office: 90 Sydney St, PO Box 38 720
Petone, Wellington, Tel: 64 4 568 4933, Fax: 64 4 568 4789
Email: sales@liquip.co.nz Website: www.liquip.co.nz