

| TM SERIES – SPECIFICATIONS | | |
|--|---|---------------------|
| Design Type: | Turbine | |
| Fitting Size: | 1/2" 3/4" 1" 1-1/2" 2" | |
| Fitting Type: | Schedule 80 Spigot (Pipe) End or NPT (Female) | |
| Flow Range: | | |
| 1/2" - TM050: | 1 - 10 GPM (3.8 - 38 LPM) | |
| 3/4" - TM075: | 2 - 20 GPM (7.6 - 76 LPM) | |
| 1" - TM100: | 5 - 50 GPM (19 - 190 LPM) | |
| 1-1/2" - TM150: | 10 - 100 GPM (38 - 380 LPM) | |
| 2" - TM200: | 20 - 200 GPM (76 - 760 LPM) | |
| Accuracy: | ± 3.0% of reading | |
| Pressure Rating: | 225 PSIG / 15.3 BAR at 73° F (23° C) | |
| Operating Temperature: | +32° F to +140° F (0° to +60° C) | |
| Typical K-Factor: | | |
| 1/2" - TM050: | 2,500 | |
| 3/4" - TM075: | 1,100 | |
| 1" - TM100: | 565 | |
| 1-1/2" - TM150: | 215 | |
| 2" - TM200: | 100 | |
| Battery Life: | 5 Years | |
| Wetted Materials: | | |
| Housing: | PVC | |
| Bearings: | Ceramic | |
| Shaft: | Tungsten Carbide | |
| Rotor: | PVDF | |
| Rings: | 316 Stainless Steel | |
| Shipping Weight (approx.): | Spigot | NPT |
| 1/2" - TM050: | .38 lbs. (.172 kg) | .55 lbs. (.249 kg) |
| 3/4" - TM075: | .43 lbs. (.304 kg) | .67 lbs. (.304 kg) |
| 1" - TM100: | .49 lbs. (.222 kg) | .49 lbs. (.381 kg) |
| 1-1/2" - TM150: | .66 lbs. (.299 kg) | 1.38 lbs. (.626 kg) |
| 2" - TM200: | .78 lbs. (.354 kg) | 1.78 lbs. (.807 kg) |
| Display Features: | Rate of Flow, Batch and Cumulative Totals, Field Calibration available. | |
| Pulse Output (-P Elec. Choice): | Open Collector (NPN) | |
| Calibration Report | Comes standard with -P (Pulse out) TM Models. N.I.S.T. – Certification available. | |

APPROVALS



Model TM150-N



"Look for the blue label!"

TM Series Meters are designed for use in water applications. The five smallest sizes are shown here. (For 3" and 4" meters, see next page.) Choose either Spigot (pipe end) or NPT fittings.



For complete part number, see "Number Reference" chart on page 46.

ACCURACY: ±3.0% READING

Features and Benefits:

- ✓ Easy to install.
- ✓ Displays in gallons, litres and cubic feet.
- ✓ Indicates Batch, Cumulative Totals and Rate of Flow.
- ✓ Available in NPT or Spigot fittings.
- ✓ Meets Schedule 80 specifications.
- ✓ Lithium battery life: 5 years.
- ✓ Non-volatile totals means amounts are retained when batteries are replaced or power is lost.

Model TM200



"Look for the blue label!"

Applications:

- OEM water treatment equipment / skids
- Small waste water treatment equipment
- Sub-metering of facility water usage
- Water based cooling systems