

Fluid Management Solutions

GOLDENROD

Fuel Tank Filters

GoldenRod Fuel Filters

GR-495 CLEAR BOWL FUEL TANK FILTER:

For removing microscopic contanimants from fuel (10 microns).

- 150 PSI working pressure High Impact plastic see-thru bowl.
- Heavy duty zinc top cap provides durability and excellent seal.
- 10 micron filter media.
- For use with petrol and diesel fuels. Water and sediment drain valve.
- 1" FBSP pipe connections.
- 100mm diameter x 242mm high.

Options: GR470-5 Replacement Element

Part No: GR495



GR-496 WATER BLOCK CLEAR BOWL FUEL TANK FILTER:

Filters and removes water from petrol and diesel fuels. 15 micron water absorbing polymer filter.

- 150 PSI working pressure High Impact plastic see-thru bowl.
- Heavy duty zinc top cap provides durability and excellent seal.
- 15 micron filter media.
- WATER-BLOCK filter blocks water from penetrating the filter and entering the fuel system.
- For use with petrol and diesel fuels. Water and sediment drain valve.
- 1" FBSP pipe connections.

Options: GR496-5W Replacement Element

Part No: GR496

GR595 SPIN-ON CANISTER FUEL FILTER:

For use with Petrol and Diesel fuels with replaceable 10 micron element.



- Maximum recommended flow rate 45 LPM.
- Ideal for farm, contractor, industrial and service station use.
- 10 micron filter media.
- Working Pressure up to 50 PSI.
- 1" FBSP Pipe Connections.
- 100mm diameter x 185mm high.

Options: GR595-5E Replacement Element

Part No: GR-595

Wellington Head Office: 90 Sydney St, PO Box 38 720

Petone, Wellington, Tel: 64 4 568 4933, Fax: 64 4 568 4789 Email: sales@liquip.co.nz Website: www.liquip.co.nz



GR596W WATER BLOCK SPIN- ON FUEL FILTER:

For use with Petrol and Diesel fuels with replaceable 10 micron removing microscopic contaminants and absorbs water from fuel.

- Low cost metal canister spin-on filter element with rugged die cast zinc top cap.
- Maximum recommended flow rate 45 LPM.
- Ideal for farm, contractor, industrial and service station use.
- Water absorbing 10 micron filter media.
- Working Pressure up to 50 PSI.
- 1" FBSP Pipe Connections.
- 100mm diameter x 185mm high.

Options: GR596-5WE Replacement Element

Part No: GR-596W



GOLDENROS

FUEL FILTER