

167 500 - 168 600



HAND HELD AIR OPERATED GREASE PUMPS

High pressure, 60:1 pressure ratio, air operated grease pumps. They can be connected to a compressed air line or to the air brake circuit of a commercial vehicle. Delivery: 1 cc. each time the trigger is pressed. Maximum air pressure: 10 bar, Air connection thread 1/4" BSP (F).

167 500, 1.000 cc. air operated grease pump

Includes a 1.000 cc barrel with an air driven grease follower. Recommended for high viscosity grease and low temperatures. Supplied with 400 mm double steel braid reinforced outlet hose with 4 jaw connector (PN 140 040) and filler nipple. Bulk grease loading using a grease filler pump.

168 600, 500 cc. air operated grease pump

Includes a 500 cc barrel with a spring driven grease follower. Three way loading: 400 g (14 oz) grease cartridges, bulk grease suction or with a grease filler pump. Supplied with filler nipple and 400 mm double steel braid reinforced outlet hose with four jaw connector (PN 140 040) and filler nipple.

168 601, 500 cc. air operated grease pump

Similar to model 168 600, includes rigid outlet stem with four jaw connector (PN 710 214).

128 003 - 128 005



FILLER VALVES AND LOADER FITTINGS

- 128 003 Grease gun filler valve**, Ø 9 mm.
- 128 033 Grease gun filler valve**, Ø 12,5 mm.
- 128 005 Grease loader fitting**
For Ø 9 mm valve. 1/4" BSP (M).
- 128 004 Grease loader fitting.**
For Ø 12,5 mm valve. 1/4" BSP (M)

108 050



GREASE GUN FILLER PUMPS

For quick, clean and easy loading of hand, air or battery operated grease guns fitted with a filler valve. Each unit includes a medium pressure lever action pump with two loader fittings that fit the more popular filling valves (Ø 9 mm and Ø 12,5 mm), drum cover and follower disc.

- 108 000 Grease gun filler pump for 12, 18 kg kegs**
Includes a 310 mm drum cover.
- 108 050 Grease gun filler pump for 20 kg kegs**
Includes a 330 mm drum cover.
- 108 100 Grease gun filler pump for 50 kg drums**
Includes a 405 mm drum cover.

108 502



FILLER PUMPS FOR CENTRALIZED GREASING UNITS

Medium pressure lever action pump with 1,5 m hose and a 2-HK (1/4") hydraulic connector for filling the reservoir of centralized greasing systems. Includes pump, cover, hose, and hydraulic connector.

- 108 501 Filler pump for centralized greasing systems, 12 - 18 kg kegs**
Includes a 310 mm drum cover.
- 108 502 Filler pump for centralized greasing systems, 20 kg kegs**
Includes a 330 mm drum cover.
- 108 503 Filler pump for centralized greasing systems, 50 kg drums**
Includes a 405 mm drum cover.

160 100



450 bar

Ni-MH

18V



Cartridge loading



Loading with filler pump (using filler valve: 128 003)

BATTERY GREASE PUMPS

160 100, 18 V NiMH battery grease pump

For use with standard grease cartridges or bulk grease. High pressure delivery, up to 500 bar (7,200 psi) and 80 g/min.

Supplied with two high capacity 18 V rechargeable NiMH batteries, 230 V quick battery charger, 1 m outlet hose with hydraulic coupler, bleeder valve and carrying strap. Pump is delivered in a heavy duty carrying case.

160 101, 18 V Li-ION battery grease pump

Same as model 160 100 but with Li-ION batteries.