

684 530

684 512

684 540

POLUX



12 AND 24 V DC DIESEL TRANSFER PUMPS, 40 LITRES / MIN

Self priming diesel transfer pumps with 12 or 24 V DC motor. Pump includes by-pass valve, built in filter (can be easily removed to clean) and carrying handle. Electric motor with IP-55 ingress protection, on/off switch and fuse. Includes 2 m cable with crocodile clamps. Inlet/outlet connection: 1" BSP (F) or flange coupling.

684 530 Diesel transfer pump. 12 V , 40 l/min

684 531 Diesel transfer pump. 24 V , 40 l/min

12 AND 24 V DC DIESEL TRANSFER PUMP KITS, 40 LITRES / MIN

12 or 24 V diesel transfer pumps equipped with 4 m x 19 mm delivery hose, aluminium delivery nozzle and 2 m cable with crocodile clamps.

684 512 Diesel transfer pump kit, 12 V, 40 l/min

684 524 Diesel transfer pump kit, 24 V, 40 l/min

12 AND 24 V DC DIESEL TRANSFER PUMPS WITH METER, 40 LITRES / MIN

12 or 24 V diesel transfer pumps equipped with a three digit meter for diesel and 2 m cable with crocodile clamps. Meter is flange coupled to the pump and includes a 90° swivelling outlet.

684 540 Diesel transfer pump with meter. 12 V , 40 l/min

684 541 Diesel transfer pump with meter. 24 V , 40 l/min



Wellington Head Office: 90 Sydney St, PO Box 38 720
Petone, Wellington, Tel: 64 4 568 4933, Fax: 64 4 568 4789
Email: sales@liquip.co.nz Website: www.liquip.co.nz

Options: (not included in PN 684 530 / 684 531, some options included in other kits as per above texts).

- **689 030:** 2 m x 25 mm suction hose with foot valve.
- **689 035:** Telescopic suction tube for 200 l drums.
- **689 021:** 4 m x 19 mm delivery hose. Connection threads: 1" BSP (M).
- **361 000:** Aluminium delivery nozzle. 1" BSP (F).
- **688 300:** Automatic delivery nozzle, 60 l/min. 1" BSP (F).
- **680 300:** Volume meter for diesel. Connection threads: 1" BSP (F). 10 bar maximum working pressure.
- **689 044:** 90° swivelling connection, 1" BSP (MF), to connect a delivery hose to the meter outlet.