

RM-12 DOUBLE PEDESTAL DOUBLE ARM HOSE REELS

10 METERS MAXIMUM HOSE CAPACITY

501 200

FLUIDS HANDLED


- Air.
- Water.
- Antifreeze Solutions.
- Synthetic and Mineral Oils.
- Grease.

MARKETS / APPLICATIONS

- Car and truck dealers.
- Service shops.
- General manufacturing.
- Service stations.
- Quick lubes.

MOUNTING

- Floor.
- Wall.
- Ceiling.
- Tank.



Dimensions mm (inches)

Full metal hose reels, can handle up to 10 m x 1/2" hose.



04

HOSE REELS

- Fatigue resistant steel spring for years of durable performance and even load when pulling and recoiling the hose.
- Full metal double pedestal arm construction, epoxy powder coated for increased wear resistance.
- Forged brass shaft ensures a leak free operation.
- Hose reels with hose include 0,8 m inlet hose.

| PART No. | BARE REEL | HOSE IN Ø | HOSE LENGTH | CONNECTING HOSE INLET | DELIVERY HOSE OUTLET | PRESSURE RATING | WEIGHT (With hose) |
|---|-----------|-----------|-------------|-----------------------|----------------------|-----------------|--------------------|
| AIR / WATER / ANTIFREEZE SOLUTIONS | | | | | | | |
| 501 100 | 501 198 | 3/8" | 10 m | 1/2" BSP (M) | 1/4" BSPT (M) | 15 bar | 17,9 kg |
| MINERAL AND SYNTHETIC LUBRICANTS | | | | | | | |
| 501 200 | 501 298 | 1/2" | 10 m | 1/2" BSP (M) | 1/2" BSP (M) | 160 bar | 20 kg |
| GREASE | | | | | | | |
| 501 300 | 501 398 | 1/4" | 10 m | 1/2" BSP (M) | 1/4" BSP (M) | 350 bar | 19,2 kg |

Bare reels include hose stopper, swivel and connection adaptors.



Reel with arms in ceiling mounting position.

Wellington Head Office: 90 Sydney St, PO Box 38 720
Petone, Wellington, Tel: 64 4 568 4933, Fax: 64 4 568 4789
Email: sales@liquip.co.nz Website: www.liquip.co.nz